



\* shackles & indicators optional



## OCSD Series

### FEATURES

- Fast resolution switching
- 25mm 5 digits LCD display w/ backlight
- Peak Hold function
- Accurate Class up to 0.1%
- 2 Programmable set-point
- Unit switch: kg / lb / t / N / kN
- Auto power-off function
- Matches with standard shackles
- Must have one of the indicators to calibrate and/or change parameters

### OPTION

- Wireless Indicator (P180)
- Wireless Handheld Indicator (380)
- Indicator / Printer (P580)
- Galvanized shackle hook (SBX)
- Scoreboard (BD)
- Infrared Remote Control

Model	OCSD	OCSD
Type	Dynamometer	Dynamometer
Accuracy Class	OIML III	OIML III
Enclosure	Aluminum	Alloy Steel
Display	25mm LCD w/ Backlight	25mm LCD w/ Backlight
Capacity Available	1 / 2 / 3 / 5 t	10 / 20 / 30 / 50 / 100 / 200 t
Battery Life	50 Hours	50 Hours
Battery	3 x AA	3 x AA
Infrared Remote Control	No	No

Rated Capacity	Division (kg/lb)	H (mm/in)	L (mm/in)	W (mm/in)	H1 (mm/in)	W1 (mm/in)	C (mm/in)	N.W. (kg/lb)	SBX (shackle)
1t / 2Klb	0.5 / 1	245 / 9.65	112 / 4.41	37 / 1.46	190 / 7.48	25 / 0.98	20.5 / 0.81	1.6 / 3.53	3.25t
2t / 4Klb	1 / 2	260 / 10.24	123 / 4.84	37 / 1.46	195 / 7.68	30 / 1.18	24 / 0.94	2.1 / 4.63	4.75t
3t / 6Klb	1 / 2	260 / 10.24	123 / 4.84	37 / 1.46	195 / 7.68	30 / 1.18	24 / 0.94	2.1 / 4.63	4.75t
5t / 10Klb	2 / 5	285 / 11.22	123 / 4.84	54 / 2.13	210 / 8.27	34 / 1.34	27 / 1.06	2.7 / 5.95	6.5t
10t / 20Klb	5 / 10	320 / 12.60	120 / 4.72	54 / 2.13	230 / 9.06	-	41 / 1.61	10.4 / 22.93	13.5t
20t / 40Klb	10 / 20	375 / 14.76	128 / 5.04	71 / 2.80	260 / 10.24	-	54 / 2.13	17.8 / 39.24	25t
30t / 60Klb	10 / 20	420 / 16.54	138 / 5.43	79 / 3.11	280 / 11.02	-	60 / 2.36	25 / 55.10	35t
50t / 100Klb	20 / 50	465 / 18.31	150 / 5.91	101 / 3.98	305 / 12.01	-	74 / 2.91	39 / 86	55t
100t / 200Klb	50 / 100	570 / 22.44	190 / 7.48	129 / 5.08	366 / 14.41	-	99 / 3.90	91 / 200.6	120t
150t / 300Klb	112	645 / 25.39	230 / 7.06	136 / 5.35	400 / 15.15	-	112 / 4.41		150t
200t / 400Klb	100 / 200	720 / 28.35	265 / 10.43	180 / 7.09	440 / 17.32	-	135 / 5.31	210 / 463	Call

\*Dimensions and specifications are subject to change without notice.